

Datavideo SE-2800 8 or 12 Input HD/SD AV Switcher

www.datavideo.info

8 or 12 Input HD/SD AV Switcher SE-2800













The Datavideo SE-2800 is a cost-effective,

broadcast-quality switcher. Featuring 8 or 12 digital and analogue inputs, it is designed for live events and TV programmes that need to blend a variety of video and audio sour ces. Thanks to its small form factor, the SE-2800 is ideal for use in a portable rack unit or in outside broadcast vehicles.

Producing superb 4:2:2 10 bit broadcast quality pictures with versatile input/output configurations, the SE-2800 also has powerful, easy to use effects, such as dual picture in picture (PIP), downstream keyer (DSK) and logo insertion.



- Supports 8 or 12 HD or SD Inputs in a variety of configurations:
- -HD Mode
- 1) 8 / 12 HD-SDI

Features

- 2) 6 / 9 HD-SDI + 2 / 3 HDMI
- -SD Mode
- 1) 8 / 12 SD-SDI
- 2) 4 / 6 SD-SDI + 4 / 6 composite video (CVBS)
- 3) 4 / 6 SDI +2 / 3 HDMI + 2 / 3 CVBS
- 3 SDI Outputs assignable to AUX, Program (PGM), Preview (PVW) or PGM clean - Built-in SD down-scaler on CH-3 SDI output
- 2 HDMI outputs for multiview monitoring
- Audio I/O
- -Input: 4 analogue balanced XLR
- -Output: 2 analogue balanced XLR. Supports embedded audio SDI output from 4-CH XLR Audio input
- Two DSK, supports Key and Fill
- Cut, Mix and Wipe with borders
- Clock on screen
- Countdown counter on multiscreen
- Two PIP displays with user-defined borders
- Tally, GPI interface and RJ45 for firmware upgrade
- DC 12V operation voltage, available for mobile use

Mainframe Front



Dual-Screen Multiscreen Viewer As Standard

Multiscreen monitoring is available on two HDMI monitors (not supplied). They can be used to monitor video and audio in a number of different configurations. For each set up, embedded audio level indication is available on all inputs and the Program window.

Configuration 1.



- On screen 1: 9 live inputs
- On screen 2: 3 live inputs with additional Preview and Program windows

Configuration 2



- On screen 1: 12 live inputs with additional Preview and Program windows
- On screen 2: Program window

Configuration 3.



- On screen 1: 8 live inputs with additional Preview and Program windows
- On screen 2: Program window

Control Panel



Mainframe Connections



Specifications


■ Video format

SD(480/59.94i,576/50i), HD (1080/59.94i, 1080/50i)

■ Video Processing

Y:Cb:Cr, 4:2:2, 10-bit SMPTE 259M-C (270 Mbps, 525/625 component video) SMPTE 292M (1.485, 1.485/1.001 Gbps)

- Genlock Mode
 Blackburst or tri sync input
- Remote Control RS-232
- Operating Temperature 0°C~50°C



dataviceo Sharing the Value

Datavideo Worldwide Offices

Datavideo Technologies Co. Ltd 10F. No. 176, Jian 1st Rd., Chung Ho City Taipei Hsien 235, Taiwan,

R.O.C. Tel: +886-2-8227-2888 Fax: +886-2-8227-2777 E-mail:service@datavideo.com.tw

Datavideo Technologies China Co

102, No.1301, Gonghexin Rd, Zhabei District, Shanghai, China

Fax: +86 21-5603 6770 E-mail:service@datavideo.cn

Datavideo Hong Kong Ltd

G/F.,26 Cross Lane Wanchai, Hong Kong

Tel: +852-2833-1981 Fax: +852-2833-9916 E-mail:info@datavideo.com.hk

Datavideo Corporation

7048 Elmer Avenue. Whittier, CA 90602,

Tel:+1-562-696 2324 Fax:+1-562-698 6930 E-mail:contactus@datavideo.us

Datavideo Technologies (S) PTE Ltd

No. 178 Paya Lebar Road #06-03 Singapore 409030 Tel:+65-6749 6866 Fax:+65-6749 3266 E-mail:sales@datavideo.sg

Datavideo Technologies India Pvt Ltd A-132, Sec-63,Noida-201307, INDIA

Tel:+91-120-2471023 Fax:+91-120-2406143 E-mail: sales@datavideo.in

Datavideo Technologies Europe BV

Floridadreef 106 3565 AM Utrecht, The Netherlands Tel:+31-30-261 96 56 Fax:+31-30-261 96 57 E-mail:info@datavideo.nl

Datavideo UK Limited

Units1 & 2 Waterside Business Park Hadfield, Glossop, Derbyshire SK13 1BE, UK Tel:+44-1457 851000 E-mail:sales@datavideo.co.uk

Datavideo France s.a.r.l

Cité Descartes 1,rue Albert Einstein Champs sur Marne

Tel:+33-1-60370246 E-mail: info@datavideo.fr

Datavideo Distributor / Reseller: