

Prism Mobile Backpack: 4K Bonding Encoder Backpack for IP Video

Supercharge your Prism Mobile with the Prism Mobile Backpack, our latest accessory that packs up to 4 additional high-performance Node 5G modems for unbeatable cellular connectivity in the field. That means you can stream over 6 cellular connections simultaneously for the ultimate on-the-go streaming experience.



MODELS

NOTE: The Prism Mobile Backpack is available in V Mount or Gold Mount.

- Prism Mobile Backpack - 2x LTE Node
- Prism Mobile Backpack - 2x 5G Node
- Prism Mobile Backpack - 4x 5G Node

BONDING MODULE

Support for up to 4 additional Node Modems using 5-pin connectors and external power.

SUPPORTED MODEMS

- Node II
- Node II CBRS
- Prism Mobile Backpack - 4x 5G Node

POWER INPUT

Requires external power from standard PTAP adapter, Gold, V-Lock Battery Plates **NOTE: 26V IS NOT SUPPORTED.**
Recommended Battery: **Anton Bauer Batteries**

INCLUDED POWER SUPPLY

16.8V 3.0A PTAP power adapter

TERADEK Prism Mobile

Prism Mobile: 4K H.264/HEVC Encoder for IP Video

Prism Mobile is the lightest LTE enabled video encoder on the market. With a flexible I/O and a compact, low-SWaP design, Prism Mobile easily fits into any workflow.

Prism Mobile gives you 4K 10-bit HDR video transmission with integrated LTE network bonding for live coverage from any location. Prism Mobile is designed to seamlessly fit onto the back of your ENG or professional camera or placed directly on a table top.

Prism Mobile can encode up to 4Kp60 video with stunning 10-bit 4:2:2 image fidelity paired with Stereo or 5.1 surround sound. The Prism platform supports many common streaming protocols such as MPEG-TS, RTSP/RTP, RTMPS, and SRT, and can be connected to Teradek's Core Cloud Platform for even more flexibility.



VIDEO

| | |
|-----------------------|---|
| Video Inputs | 1x 12G/6G/3G/HD/SD-SDI (75 Ω BNC), 1x HDMI 2.0 Type-A receptacle |
| Video Outputs | 1x 12G/6G/3G/HD/SD-SDI (75 Ω BNC) |
| Supported Resolutions | 4K DCI p23.98/24/25/29.97/30/50/59.94/60 4K UHD UHD p23.98/24/25/29.97/30/50/59.94/60 1080p 23.98/24/25/29.97/30/50/59.94/60 1080i 50/59.94/60 1080PsF 23/24/25/29/30 720p 50/59.94/60 576i 480i |

VIDEO PROCESSING

| | |
|---------------------------------|--|
| Video Compression/Decompression | ISO MPEG-4 Part 10: Advanced Video Coding (AVC)/ITU H.264 AVC: Baseline, Main, High ISO MPEG-H Part 2: High Efficiency Video Coding (HEVC)/ITU H.265 HEVC: Main |
| Supported Video Bitrate | 250 Kbps to 85 Mbps |
| Video Format Conversion Support | Built in video scaler and deinterlacer |
| HDR Support | Yes (Rec. 2100) |
| Color Correction | CDL/1024 1D LUT (supports 10-bit color), 33x33x33 3D LUT (supports 10-bit color) |
| Bonding | Support for up to 9 network inputs: 4x Cellular phones 2x Internal Node modems 1x External modem 2x Ethernet networks |
| Recording | Supported File Type - MP4, TS wrapper Supported Media - SD Card, USB, NFS |

PROTOCOL SUPPORT

| | |
|-------------------------------------|---|
| Network Protocols | TCP/IP, UDP, HTTP, DHCP, NTP, SSL, IGMP |
| Supported Video Transport Protocols | Secure Reliable Transport (SRT), RTMP/RTMPS, MPEG-TS (UDP, TCP, TCP Server, Multicast), CDNs (YouTube, Facebook, Vimeo), RTSP/RTP |
| Remote Management | Teradek Core |

AUDIO

| | |
|-------------------|---|
| Audio Support | Stereo, 5.1 surround sound |
| Audio Compression | AAC-LC |
| Audio Bitrate | 32kbps to 512kbps |
| Audio Sample Rate | 48kHz |
| Audio Input | Embedded over SDI and HDMI, 3.5mm TRRS Stereo Line Level Analog or Microphone in, adjustable gain |
| Audio Output | 3.5mm TRRS Stereo Headphone output, adjustable gain |

PHYSICAL ATTRIBUTES

| | |
|------------------|--|
| Dimensions | 5.9"W x 3.9"D x 1.3"H [162 x 92 x 35mm] |
| Weight | 23.4oz [664g] without plates; 30.5oz (864g) with plates |
| Construction | Milled aluminum |
| Mounting Options | Camera-back, Gold, Gold 26V and V-Lock mounts, Can be mounted using the 1/4" 20 mounting holes |

INTERFACES

| | |
|-----------------------------|---|
| Configuration Interface | <ul style="list-style-type: none">• Feature-rich Web UI for local device management, configuration, and control• Intuitive iOS configuration app (Prism App)• OLED Status Display w/ Nav control buttons• Core for cloud-based device management |
| Cellular | 2x Internal Node II 4G LTE modems (Verizon Certified - Global Use) with dual switchable SIM slots, Supports Teradek Data and up to 4 cellular SIM cards |
| USB Interface Functionality | 1x Powered locking connector with Node Modem support 1x Powered USB-A with external storage support |
| Ethernet | 2x 10/100/1000 BASE-T Gigabit Ethernet (RJ45) |
| Wireless | WiFi: 2.4/5GHz 802.11 a/b/g/n/ac/ax MiMo |

POWER

| | |
|---------------------------|--|
| Power Input | 2-pin circular locking connector, Gold, Gold 26V and V-Lock Battery Plates |
| Voltage | 6-28V DC |
| Nominal Power Consumption | 20W Nominal, 36W Max |