



* WM-701B has interfaces for both input and output of HDMI, and its unique screen division function allows connection through HDMI output interface to another screen to be used as the director monitor.

- 1 Component input (3 in the upper left)
- 2 Audio input
- 3 Video input/output
- 4 HDMI input/output
- 5 XLR interface



* WM-701B can fit different battery pinch plates based on respective needs of battery types of customers.



F970 | LP-E6 | D28 | BP 型

Parameter

Product Type	WM-701B
Screen Size	TFT LCD 7.0inch 1843200 Pixels
Display Screens	TFT LCD
Resolution	1024*600
Resolution up to	1920*1440 
Line Frequency Range	30-60kHz
Field Frequency Range	60Hz ~ 75Hz
Dot Pitch	0.05 (W) x 0.15 (H)
Screen Ratio	16: 9
Luminance	250 cd/ m ²
Contrast Ratio	700:1
Response Time	10ms
Viewing Angle	75° /75° (L/R) 70° /75° (U/D)
Backlight Device	LED
Input Signal	HDMI、YPbPr、VIDEO、AUDIO
Format Supported by HDMI and YPbPr	480i、480p、576i、576p、720p、1080i、1080p
Video Color System	PAL-4.43; NTSC-3.58
Loudspeaker Output Power	≥ 1W/8 Ω
Input Voltage	DC6-24V
Watt Consumption	≤ 6w
Standby Current	≤ 50mA
Dimensions	188mm (L) *134mm (W) *42mm (H)
Weight	446g
Working Temperature	- 20 ~ 55℃
Preserve Temperature	-30℃ ~ 65℃

Features

Function \ Type	WM-700A	WM-700B	WM-700C	WM-700D-SDI	WM-701B
1. Push-To-Talk adjusting		●	●	●	●
2. Multi-picture selecting			●	●	
3. Self-defined color temperature			●	●	●
4. AC & DC Applicable	●	●	●	●	●
5. Safe frame setting		●	●	●	●
6. Matte box protecting	●	●	●	●	●
7. Auxiliary focusing		●	●	●	●
8. Monocolor, black and white and multicolor shortcut keys		●			●
9. Tally function			●	●	

HD Monitor | WM-701B | Accessories