Contact Us Search Site

P

Manfrotto .COM





 Products
 Photo
 Video
 Lighting
 Bags
 Apparel

 News & Events
 Service
 Media Center
 Local Heroes
 Social Media
 About Us

You Are Here: Home

Video Heads

Pro

PRO VIDEO HEAD 100



PRO VIDEO HEAD 100

WHERE TO BUY

Part # 509HD REPLACES PART # 516, 519

Μου αρέσει!

Tweet 1

3

METRIC IMPERIAL

Select to compare

VIEW SIMILAR PRODUCTS

509HD - PRO VIDEO HEAD 100

•

DESCRIPTION

SPECIFICATIONS

VIDEOS

SPARE PARTS

The 509HD is the result of an important technical evolution - the perfect synthesis between an innovative "bridge architecture" and Manfrotto's cutting edge engineering. Bridging Technology - an exclusive Manfrotto patent. A new bridge leading the videographer and photographer to even better results with today's high-definition cameras. The 509HD's FDS (Fluid Drag System) is based on variable fluid cartridges on both, TILT and PAN axes; the ergonomics of the controls have been noticeably improved to make use of the FDS even easier. Movement around the axes is smoothed by ball-bearing units which remove all unwanted vibration. All of this guarantees ultimate control and excellent video camera support, no matter what the situation, the shooting style, or the equipment set-up. The load capacity has also been improved: the 509HD supports kit up to 28.8lb (13kg) at 55mm c.o.g and two 3/8" threads on the top plate allow accessories, such as monitors and arms, to be fitted straight to the head, thus eliminating the need for extra clamps, saving set-up time and freeing the video camera's hot shoe for other components. 509HD features the ABR (Advanced Balancing Recorder) for precision when fixing equipment, ensuring a perfect balancing position, saving time and making this operation much more efficient, accurate and fast. The system can be leveled thanks to the Ø100mm half ball and the illuminated leveling bubble. Systems available with aluminium twin legs tripods (middle spreader or ground spreader) or carbon fibre single tubes tripod.

SPE	CIFICATIONS		METRIC	IMPERIAL
	additional pan handle	509HLV		
	attachment	3/8" male thread attachment type		
	attachment number	1/4" and 3/8" screws attachment type		
	balance control	4 step: 0kg - 4.3kg - 8.65kg - 13kg		
•	front tilt	-60° / +90° tilt range		
	half ball diameter	100.0 mm		
	independent pan lock	yes		
	independent tilt lock	yes		
	levelling bubble	illuminated		
	material	aluminum		
	maximum working temperature	60.0 °C		
	minimum working temperature	-20.0 °C		
	pan bar positions	2 number		



You might also like:



Distributors Area . Extranet . Home . Affiliate Program . Careers . Sitemap . Contact Us . Legal . Privacy . Terms of Use

Like

Giannis Alexiou, Kampas Dimitris and 45,255 others like this.









© 2010 VitecGroup Italia Spa — Manfrotto is a registered trademark of Lino Manfrotto + co. Spa

Lino Manfrotto + Co., S.p.A. (VAT N° 020 847 402 46) | Vitecgroup Italia Spa (VAT N° 028 860 301 68) $\,$

Manfrotto's Local Websites Worldwide Global | Canada | Schweiz DE | Schweiz FR | 中国 | Deutschland | France | 香港 | India | Italia | 日本 | United Kingdom | United States