

## SOUND LIKE YOU MEAN IT.





# UNPLUGGED. UNCOMPROMISING.

Performance Gear® Wireless Systems feature advanced wireless technology engineered to uncompromising Shure standards. For performers who manage their own sound, nothing could be easier. Application-specific mics. Your choice of wireless systems that find an open channel with the touch of a button and wired mics that come complete with all the accessories you need.

The first professional choice for freedom from the wire

- Choose from up to 10 channels per system at the touch of a button.
- Use up to 8 systems simultaneously (multiple UHF bands).\*
- Microprocessor-controlled Internal Antenna Diversity. Innovative internal antenna design means damage or misalignment are things of the past. Monitors signal strength, adjusting automatically for continuous reception.







<sup>\*</sup> Up to 9 simultaneous systems possible with available US & China frequency bands. Please consult your local Shure representative for details.

#### **Wireless Systems**





















				•
			-	-
100	-000	0	-	
 10 1000			_	

Wireless Vocal	Wireless Guitar	Wireless Lavalier	Wireless Headset  PG30 Headset Microphone System  Comfortable, reliable headworn mic for active users.  PG30TQG Headset Condenser PG1 Bodypack Transmitter PG4 Diversity Receiver	
PG58 Handheld Microphone System	Guitar/Bass System	PG185 Lavalier Microphone System		
A rugged mic tuned to accentuate the clarity of lead and backup vocals.	Rugged guitar system for any electronic instrument with 1/4" outputs.	Reliable wearable mic for spoken word applications.		
PG2/PG58 Handheld Mic PG4 Diversity Receiver	WA302 Instrument Cable PG1 Bodypack Transmitter PG4 Diversity Receiver	PG185 Lavalier Mic PG1 Bodypack Transmitter PG4 Diversity Receiver		
	()))() ())())			
60 Hz – 15 kHz		50 Hz – 20 kHz	40 Hz – 20 kHz	



Dual Vocal Microphone System



PG88 Dual Receiver Included with all Combo Systems.



Vocal/Lavalier PG1288/PG185



Dual Vocal PG288/PG58



Vocal/Headworn PG1288/PG30



Dual Lavalier PG188/PG185



Key Operating Principle



Polar Pattern Cardioid






Frequency Response

### **Technical Specifications**

Note: All specifications are subject to change.

#### Performance Gear® Wireless



- Available Frequencies: between 536 865 MHz (available frequencies depend on applicable regulations in country where system is used)
- Operating Range: 250 ft. (75m) under typical conditions
- Audio Frequency Response: 45 to 15,000 Hz +/- 4 dB (overall system frequency response depends on microphone element)
- Transmitter RF Output Power: 10 mW typical
- Audio Output Connector: XLR balanced and 1/4" unbalanced
- Maximum Output Level: -19 dBV (XLR), -5 dBV (1/4") (ref. +/- 33 kHz deviation, 1 kHz tone)
- Battery Life: up to 8 hours with a 9V battery
- Dynamic Range: >100 dB, A-weighted
- System Distortion: .5% typical (ref. +/- 33 kHz deviation, 1 kHz modulation)

Note: Performance may vary depending on country regulations and operating environment.



#### Rear panel





⊙ 。




Top view

#### PG88 Dual Receiver

Up to 8 compatible systems\* 1/4" and XLR audio outputs Microprocessor-controlled internal antenna diversity

#### PG4 Diversity Receiver

Up to 8 compatible systems\* 1/4" and XLR audio outputs Microprocessor-controlled internal antenna diversity



Power, mute and battery status LED Power and mute switch Power lockout 9V batteries (included) provide 8 hours of continuous use 250 ft. (75m) operating range



**United States:** 

Shure Incorporated 5800 West Touhy Avenue Niles, IL 60714-4608 USA

Phone: 847-600-2000 Fax: 847-600-1212 Email: info@shure.com Europe, Middle East, Africa:

Shure Europe GmbH Wannenäckerstr. 28, 74078 Heilbronn, Germany

Phone: 49-7131-72140 Fax: 49-7131-721414 Email: info@shure.de Asia, Pacific:

Shure Asia Limited 3/F, Citicorp Centre 18 Whitfield Road Causeway Bay, Hong Kong

Phone: 852-2893-4290 Fax: 852-2893-4055 Email: info@shure.com.hk Canada, Latin America, Caribbean:

Shure Incorporated 5800 West Touhy Avenue Niles, IL 60714-4608 USA

Phone: 847-600-2000 Fax: 847-600-6446 Email: international@shure.com