





The LCMAX Connector

The LC-MAX is 100% compatible with standard LC sockets, connecting to your equipment without the need for an adapter cable or bulkhead.





100% compatible LC

Highest quality engineering

IP68 Cap & Tether

Capacity per Reel (m)

	Number of Fibres	2	4	8	12
	Cable Dia.	5.4mm	5.8mm	6.4mm	7.3mm
	GT235	76	67	55	43
OPTION	GT310	141	123	102	79
	GT380	277	241	199	154
	HT385	447	390	322	249
	HT485	710	618	511	396

Note: Larger capacity reels are available.

Cable Comparison

	Number of Fibres	2	4	8	12		
	Cable Dia.	5.4mm	5.8mm	6.4mm	7.3mm		
NO	Weight/km	26kg	30kg	37kg	45kg		
CATION	Tensile Strength Short Term	300N	400N		410N		
SPECIFI	Operating Temperature	-55°C to +85°C					
dS	Crush Long/Short Term	3000N/m / 5000N/m (IEC 60994-2-20)					

Features

- Rugged metal bodied LC
- IP68 protected from dust and water
- Quality Belden Tactical fibre cable
- Compact, portable cable reels
- Mates directly with standard LC socket
- 2 & 4 core fibre (8 & 12 coming soon)
- Available in both Multi and Single Mode
- Snag-free protective cap
- Excellent cable retention
- Lightweight and easy to carry
- Manufactured in the UK
- After care service

To see our other ArmourLux ranges, to request an ArmourLux sample or for more information call: 01488 685 800 or email: info@armourlux.com



ArmourLux is a trading division of Universal Networks UK Limited Charnham Lane, Hungerford, Berkshire RG17 0EY. T: +44 (0) 1488 685800 | F: +44 (0) 1488 685899 | www.armourlux.com



